



PRODUCTION RANGES RODS

STANDARDS			ROUND RODS			HEXAGONAL RODS			SQUARE RODS		
			Ø DIAMETER (mm)			WIDTH BETWEEN PARALLEL SIDES (mm)			WIDTH BETWEEN PARALLEL SIDES (mm)		
EN NORM	EN SYMBOL	ASTM	COLD DRAWN		EXTRUDED	COLD DRAWN		EXTRUDED	COLD DRAWN		EXTRUDED
			MIN	MAX	MAX	MIN	MAX	MAX	MIN	MAX	MAX
CW614N	CuZn39Pb3	C38500	6	55	110	6	55	80	5	45	80
CW617N	CuZn40Pb2	C38000	6	55	110	6	55	80	5	45	80
CW600N	CuZn35Pb1	-	10	55	110	10	55	80	10	45	80
CW601N	CuZn35Pb2	C34200	10	55	110	10	55	80	10	45	80
CW602N	CuZn36Pb2As	C35330	10	55	110	10	55	80	10	45	80
CW603N	CuZn36Pb3	C36000	6	55	110	6	55	80	6	45	80
CW606N	CuZn37Pb2	C35300	8	55	110	8	55	80	8	45	80
CW607N	CuZn38Pb1	-	8	55	110	8	55	80	8	45	80
CW608N	CuZn38Pb2	C35000	6	55	110	6	55	80	6	45	80
CW611N	CuZn39Pb1	-	8	55	110	8	55	80	8	45	80
CW612N	CuZn39Pb2	C37700	6	55	110	6	55	80	6	45	80
CW613N	CuZn39Pb2Sn	-	6	55	110	6	55	80	6	45	80
CW616N	CuZn40Pb1Al	-	6	55	110	6	55	80	6	45	80
CW626N	CuZn33Pb1,5AlAs	-	10	55	110	10	55	80	10	45	80



PRODUCTION RANGES HOLLOW RODS

STANDARDS			ROUND HOLLOW RODS			POLYGONAL HOLLOW RODS			INSIDE DIAMETER		
			Ø DIAMETER (mm)			WIDTH BETWEEN PARALLEL SIDES (mm)			Ø DIAMETER (mm)		
EN NORM	EN SYMBOL	ASTM	COLD DRAWN		EXTRUDED	COLD DRAWN		EXTRUDED	COLD DRAWN		EXTRUDED
			MIN	MAX	MAX	MIN	MAX	MAX	MIN	MAX	MAX
CW614N	CuZn39Pb3	C38500	26	65	70	22	60	70	12	55	55
CW617N	CuZn40Pb2	C38000	26	65	70	22	60	70	12	55	55
CW602N	CuZn36Pb2As	C35330	26	65	70	22	60	70	12	55	55
CW603N	CuZn36Pb3	C36000	26	65	70	22	60	70	12	55	55
CW608N	CuZn38Pb2	C35000	26	65	70	22	60	70	12	55	55
CW612N	CuZn39Pb2	C37700	26	65	70	22	60	70	12	55	55